


REV. #	DESCRIPTION	DATE	BY
X	X	X	X

DESCRIPTION OF EQUIPMENT

- ① DRIVE UNIT -SHAFT MOUNT, * HORSEPOWER 230/460 VOLT, 3 PHASE, 60 HZ.
- ② DRIVE SHEAR PIN SPROCKET
- ③ DRIVEN SPROCKET
- ④ DRIVE CHAIN
- ⑤ CHAIN GUARD
- ⑥ LIMIT SWITCH
- ⑦ HEADSHAFT-IDLERSHAFT BEARINGS
- ⑧ HEADSHAFT- IDLERSHAFT SPROCKETS
- ⑨ CARRYING CHAIN
- ⑩ RAKE
- ⑪ BAR RAKE
- ⑫ DEAD PLATE
- ⑬ HEADFRAME
- ⑭ RETURN RAIL
- ⑮ WIPER-WITH PVC WIPER BLADE, AND SHOCK ABSORBER
- ⑯ ANCHOR BOLTS

NOTE: DRAWING IS PRELIMINARY. DIM. NOTED WITH A * CAN BE CHANGED TO SUIT DESIGN REQUIREMENTS.

THIS DOCUMENT AND DRAWINGS, SPECIFICATIONS AND OTHER INFORMATION SET FORTH THEREON ARE THE EXCLUSIVE PROPERTY OF E & I CORP., AND DUPLICATION OR USE OF SUCH DATA BY OTHERS IS PROHIBITED. THE MERE FACT THAT THIS DOCUMENT MIGHT BE SUBMITTED TO OTHERS FOR WHATEVER PURPOSE, OR IS REQUIRED TO BE FILED OF PUBLIC RECORD, SHALL NOT BE A WAIVER OF COMPLETE AND EXCLUSIVE OWNERSHIP BY E & I CORP.



E & I CORPORATION
A Division of McNish Corporation
COLUMBUS, OHIO 43229

EQUIPMENT TWO SHAFT CATENARY BAR SCREEN- 30 DEG.					
CUSTOMER X					
SCALE X	DRAWN BY TAS	DATE 12-20-01	CHECKED BY FOX	DATE 12-20-01	DRAWING NO. 40020